

Quality Access Doors- FAST!

APPLICATION

Acudor Electric Actuation Roof Hatches are designed to provide convenient, economical access to the roof of a building with the ease of automation. By adding an electric actuator, our hatch can be opened and closed remotely. This feature is available on small ladder access hatches, and more importantly on larger equipment hatches, which are typically heavy and difficult to operate.

FEATURES

- Choice of operating switch and/or remote control
- 12V/24V DC Electrical Actuator. Suitable for mains supply AC 120V/60Hz or 230V/50Hz
- · Can open to any angle up to 80 degrees max
- · Battery back-up
- Synchronized operation for large sizes

OPTIONAL FEATURES

- · Stainless Steel Hardware
- Louvered Curbs
- Curb Mounted Units
- Curb pitch corrected for sloped roof

SPECIFICATIONS

COVER: Double-skin construction ("in box type design") with 1" cellulose insulation and a continuous EPDM foam weather/draft seal gasket that is attached to the inside of cover to provide a flush, tight fit. Designed to support a live load of 40lbs./sq. ft

CURB: 1" thick fiberboard roof insulation at curb exterior. Curb is 12" high, with 3.375" wide bottom flange and pre-drilled mounting holes

OPENING: Convenient electric actuation with options of Push Button Switch, Key Switch and/or Remote Control. Can be kept open at any angle for ventilation. Single covers with more than one actuator operate on synchronous mode. Hatches with more than one cover have at least two actuators which need to be operated in sequence. Battery back-up is provided for emergency exits to ensure power supply in case of power outage. Control Box keeps the batteries charged.

DOOR LATCH: Self Locking feature of Electric Actuator replaces need for conventional locks in standard designs Additional locking arrangements available upon request.

FINISH: Aluminum: Mill Finish grey paint.

For a complete list of options visit www.BestAccessDoors.com





To view Pricing and Additional Product Info.

SUBMITTAL/TECHNICAL DATA SHEET

SKU: **BA-ALRF** ALUMINUM ELECTRIC ACTUATION ROOF HATCH




■ DIMENSIONS AND APPEARANCE

>> CLICK TO VIEW ADDITIONAL DETAILS AND PRICING <<

STANDARD SIZES:

STANDARD SIZES.						
MODEL	CURB ID L&W INCHES (MM)	WEIGHT LBS KG				
EA3232	24 x 24 (610 x 610)	60 27.3				
EA3244	24 x 36 (610 x 914)	70 31.8				
EA3838	30 x 30 (762 x 762)	75 34.0				
EA3844	30 x 36 (762 x 914)	85 38.6				
EA3862	30 x 54 (762 x 1372)	135 61.4				
EA3804	30 x 96 (762 x 2438)	245 111.4				
EA4444	36 x 36 (914 x 914)	95 43.2				
EA5656	48 x 48 (1219 x 1219)	115 52.0				

(Special sizes up to 197" x 197" available upon request)



PROJECT DATA

Custom Sizes Available - Fast!

	PROJECT NAME:	QTY	W	Н	OPTIONS	
	ARCHITECT:					
2	DEALER:					
	CONTRACTOR:					
	LOCATION:	SPECIAL INSTRUCTIONS:				
	DATE:					
	TAGGING INSTRUCTIONS:	SUBMITTAL APPROVAL : (signature or stamp)				



TELEPHONE: 1-800-483-0823 1-888-828-6021



228 PARK AVE. S. #76520 NEW YORK, NY, 10003



WEBSITE: www.BestAccessDoors.com