




Quality Access Doors - FAST !



# RECESSED ACCESS DOOR BA-AP-5010

## Application

- Designed for use in acoustical plaster walls and ceilings

## Product Features

- Door is recessed 5/8" and is lined with self-furring lath
- Expansion casing bead with 3" wide galvanized lath

## BA-AP-5010 Access Door Specifications:

**Material:** Steel or Stainless Steel: 16 gage door, 14 gage mounting frame

**Door:** Recessed 5/8" and lined with self-furring galvanized lath

**Door Frame:** Expansion casing bead with 3" wide galvanized lath, recessed 3/4" to receive plaster

**Hinge:** Concealed, pivoting rod type. (For wall applications, a continuous exposed piano hinge is suggested.)

**Standard Latch:** Flush to surface, screwdriver operated cam latch

**Optional Latches/Locks:** Cylinder lock and key, allen head cam latch, spanner head cam latch


**Finish:** Steel: 5-stage iron phosphate preparation with prime coat of White alkyd baked-on enamel



## AVAILABLE SIZES *(Special sizes available upon request)*

NOMINAL DOOR SIZE W X H		WEIGHT PER DOOR		
inches	mm	Latches	lbs.	kg.
12 X 12	305 X 305	1	8.5	3.9
18 X 18	457 X 457	2	15	6.8
24 X 24	610 X 610	2	23	10.4
24 X 36	610 X 914	4	30	13.8

Wall or ceiling opening is W + 3/8" ( 9 mm)  
For detailed specifications see submittal sheet



[Click here to view the Products](#)