



Quality Access Doors - **FAST!**

APPLICATION

DRF flat roof access skylight is an energy-efficient hatch that acts as a skylight while providing access to flat roofs. A special opening system of patented hinges and gas springs safely open the window and secure it in the open position at 80 degrees. This window utilizes Fakro DU6 triple-pane glazing mounted on insulated multi-chamber PVC frame.

FEATURES

- Suitable for roof pitches between 2-15 degrees.
- Sound reduction index Rw 38 dB.
- The DRF roof access skylight is an energy-efficient, DU6 glazing unit with a Class P2A anti-burglary inner pane and a window U-factor= 0.23 BTU/h ft²F.
- Range of internal and external accessories available.

FRAME STRUCTURE:

Multi-chamber PVC profile insulated with polystyrene.

GLAZING:

DU6 - triple pane passive glazing with warm spacers, argon gas and two low-E coatings. Tempered external and laminated internal glass.

TERMINATION BAR:

Included aluminum profiles to secure roofing. Membrane into the skylight frame.

OPENING METHOD:

Manually, up to an angle of 80°

WARRANTY:

10 years for skylight and glazing, 2 years for gas springs.

DOOR HARDWARE:

Gas springs to facilitate operation of the sash.

SUBMITTAL/TECHNICAL DATA SHEET

SKU: **BA-DRF-DU6**

FLAT ROOF ACCESS SKYLIGHT



DIMENSIONS AND APPEARANCE


>> [CLICK TO VIEW ADDITIONAL DETAILS AND PRICING <<](#)

TECHNICAL PARAMETERS:

Technical parameters	Glazing unit type		
	Unit	DU6	Harmonised standards
U-factor for window	[BTU/h ft²F]	0.23	NFRC 100
U-factor for glazing unit	[BTU/h ft²F]	0.18	NFRC 100
SHGC		0.26	NFRC 200
Condensation resistance	-	70	NFRC 500
Visible transmittance	-	0.35	NFRC 200
Impact resistance	Class 5 - 950 mm		EN 14351 - 1:2006+A2:2016
Positive design pressure (DP)	3600 Pa (~75.19 psf)		NAFS 2011 / NAFS 2017
Negative design pressure (DP)	-3600 Pa (~-75.19 psf)		
Water penetration resistance test pressure	720 Pa (~15.04 psf)		
Canadian air infiltration/exfiltration level	A3 Level (NAFS-11)/ A3 Level (NAFS-17)		

OPTIONAL ACCESSORIES:

Mounting accessories	- The XRD/W installation base allows raising the access roof light above the roof by 6". Maximum 3 bases can be joined.
Internal accessories	- AMZ/F Solar awning blind
External accessories	- ARF/D - APF/D pleated blinds



For more detailed information check the second page

For a complete list of options visit
www.BestAccessDoors.com

PROJECT DATA

Custom Sizes Available - Fast!

Scan  or  Click



To view Pricing and
Additional Product Info.

PROJECT NAME :	QTY	W	H	OPTIONS
ARCHITECT :				
DEALER :				
CONTRACTOR :				
LOCATION :	SPECIAL INSTRUCTIONS :			
DATE :	SUBMITTAL APPROVAL : (signature or stamp)			
TAGGING INSTRUCTIONS :				

TELEPHONE:
1-800-483-0823
FAX:
1-888-828-6021



228 PARK AVE. S. #76520
NEW YORK, NY, 10003



WEBSITE:
www.BestAccessDoors.com
E-MAIL:
info@bestaccessdoors.com



BA-DRF-DU6

FLAT ROOF ACCESS SKYLIGHT

SIZE:						
Rough opening	A x B	22½" x 47"	25" x 47"	22½" x 54"	25" x 54"	30" x 55"
Outside frame	S x L	22" x 46⅝"	24½" x 46⅝"	22" x 53½"	24½" x 53½"	29½" x 53½"

