

Quality Access Doors- FAST!

Door is fabricated from 16 gauge, galvannealed steel with a white prime coat finish and 1" thick rigid foam insulation.

Frame is fabricated from 16 gauge, galvannealed steel with a white prime coat finish and provided with bolt holes.

Hinge is concealed and operates completely out of sight, so that only the door and frame are visible.

Exterior latch is a cylinder lock that features a knurled knob or key operation.

Finish is a white prime coat suitable for painting.

GUIDE SPECIFICATION

Access door frame shall be fabricated from 16 gauge galvannealed steel with a white prime coat finish and provided with bolt holes. Access door panel shall be fabricated from 16 gauge galvannealed steel with a white prime coat finish. Door shall be filled with 1" thick, rigid foam insulation and neoprene gasket on four sides. Access door shall have a concealed hinge with exterior latching cylinder lock that features a knurled knob or key operation. Finish shall be a white prime coat suitable for painting.

MODEL NUMBER AND OPTIONS SELECTION

BASE MODEL NUMBER

□ -ED Exterior Door for Walls and Ceilings

SUFFIX OPTIONS

☐ -GB Galvanized Drywall Bead
☐ -SS Stainless Steel Construction
(Type 304 No. 4 Satin Finish)

For a complete list of options visit www.BestAccessDoors.com





To view Pricing and Additional Product Info.

SUBMITTAL/TECHNICAL DATA SHEET

SKU: BA-ED

EXTERIOR DOOR FOR WALLS AND CEILINGS





■ DIMENSIONS AND APPEARANCE

>> CLICK TO VIEW ADDITIONAL DETAILS AND PRICING <<

DOOR SIZE (W X H)	CEILING OPENING (Minimum Required)	LATCHES	WEIGHT	
ED 8" x 8"	8-3/8" x 8-3/8"	1	5 lbs.	
ED 12" x 12"	12-3/8" x 12-3/8"	1	15 lbs.	
ED 14" x 14"	14-3/8" x 14-3/8"	1	17 lbs.	
ED 18" x 18"	18-3/8" x 18-3/8"	1	20 lbs.	
ED 22" x 30"	22-3/8" x 30-3/8"	2	35 lbs.	

DOOR SIZE (W X H)	CEILING OPENING (Minimum Required)	LATCHES	WEIGHT	
ED 24" x 24"	24-3/8" x 24-3/8"	1	28 lbs.	
ED 24" x 36"	24-3/8" x 36-3/8"	2	40 lbs.	
ED 30" x 30"	30-3/8" x 30-3/8"	2	38 lbs.	
ED 36" x 36"	36-3/8" x 36-3/8"	2	50 lbs.	
ED 36" x 48"	36-3/8" x 48-3/8"	2	81 lbs.	





■ PROJECT DATA

Custom Sizes Available - Fast!

	PROJECT NAME :	QTY	w	Н	OPTIONS	
	ARCHITECT:					
Sa.	DEALER:					
	CONTRACTOR:					
	LOCATION:	SPECIAL INSTRUCTIONS:				
	DATE:					
	TAGGING INSTRUCTIONS :	SUBMITTAL APPROVAL : (signature or stamp)				
1						



TELEPHONE: 1-800-483-0823 FAX: 1-888-828-6021



228 PARK AVE. S. #76520 NEW YORK, NY, 10003



WEBSITE: www.BestAccessDoors.com

info@bestaccessdoors.com