

Quality Access Doors- FAST!

DESCRIPTIONS

The access panel consists of a welded aluminum frame and is available with 1/2" (12.7 mm) or 5/8" (15.9 mm) inlayed drywall and two latches.

Both an outer and an inner frame assembly consists of high grade aluminum which is bonded with a special welding process.

For sizes 12" x 12" (305 mm x 305 mm) and up the access panels are equipped with a safety system to prevent accidental opening. This safety system must be reattached if the hatch is removed.

The reveal of 1/16 of an inch (1.59 mm) is visible between the outer frame and door hatch. The concealed snap locks open the access panel when pressure is applied to the spring loaded latch side.

This access panel is designed with a double door to create a large clear span opening.

ADVANTAGES

- Superior engineering & innovative design.
- Fast delivery.
- Quick and easy installation.
- · Solid aluminum frame.
- Flush installation in ceilings and walls
- Available in moisture / mildew resistant green board and cement board.

For a complete list of options visit www.BestAccessDoors.com





To view Pricing and Additional Product Info.

SUBMITTAL/TECHNICAL DATA SHEET

SKU: BA-F1-MULTI-DOOR DRYWALL ACCESS PANEL

OVERSIZED MULTI-DOOR



■ DIMENSIONS AND APPEARANCE

>> CLICK TO VIEW ADDITIONAL DETAILS AND PRICING <<

OPTIONS:

SD - Screwdriver operated cam latch					
FS - Screwdriver operated four-square cam latch					
Z - Round Cylinder Lock with Key					
M - Mortise Cylinder Lock Preparation					
H - Hex Head Cam Latch					
P - Pinned Hex Head Cam Latch					

Customized sizes can be produced in every dimension upon request.





PROJECT DATA

Custom Sizes Available - Fast!

	PROJECT NAME:	QTY	w	Н	OPTIONS
	ARCHITECT:				
	DEALER:				
	CONTRACTOR:				
	LOCATION:	SPECIAL INSTRUCTIONS:			
2	DATE:				
	TAGGING INSTRUCTIONS:	SUBMITTAL APPROVAL : (signature or stamp)			
1					



TELEPHONE: 1-800-483-0823 FAX: 1-888-828-6021



228 PARK AVE. S. #76520 NEW YORK, NY, 10003



WEBSITE: www.BestAccessDoors.com

info@bestaccessdoors.com