



Quality Access Doors- **FAST!**

DESCRIPTIONS

Recessed flange access panel for 3 hour wall or ceiling applications that require a trimless appearance. 5/8" deep concealed wraparound flange construction makes the frame extremely rigid.

SPECIFICATIONS

MATERIAL: Satin finish galvanized steel or 304 stainless steel.

FRAME: 16 ga (1.61mm) up to and including 30" x 48" (762mm x 1219mm) or 14ga (1.99mm) for larger sizes. Depth 3-1/4" (83mm).

FLANGE: Concealed flange is recessed 5/8" to allow for wallboard installation on top. Flange is 1-1/4" (32 mm).

DOOR PANEL: 18 ga (1.31mm), with a 22 ga (0.85mm) liner.

INSULATION: The door panel contains 2-1/2" (63mm) of high temperature insulation material.

FINISH: Rust-inhibitive off-white prime coat or # 4 polished stainless steel finish on exterior surface.

HINGES: The concealed continuous rod hinge is designed to secure the door panel. The hinge is placed on the long side of the door ("H" dimension) unless otherwise requested. Sizes greater than 48" (1219mm) in a wall application are provided with a continuous piano hinge.

PANEL CLOSER: The automatic panel closer will close and latch the door from an open position of approximately 90° as required by NFPA 80.

LATCH: Flush mount 1/4" allen key (A). All fire-rated locks are self-latching and include an interior latch.

SIZES: Minimum size (W x H) 12" x 12". Maximum size for walls is 48" x 60, Maximum for ceilings is 30" x 48".

SUBMITTAL/TECHNICAL DATA SHEET

SKU: **BA-FD3RF**

**3 HOUR FIRE-RATED
ACCESS PANEL**

WITH RECESSED FLANGE



DIMENSIONS AND APPEARANCE

>> CLICK TO VIEW ADDITIONAL DETAILS AND PRICING <<

STANDARD SIZES:

Rough Opening is Order Size W x H H = Hinge Side		No. of Latches/ Locks	Weight	
Inches	Metric (mm)		Kgs	Lbs.
3 HR WALLS OR CEILINGS				
12 x 12	305 x 305	1	6	12
16 x 16	406 x 406	1	8	17
18 x 18	457 x 457	1	10	21
22 x 22	559 x 559	1	14	29
22 x 30	559 x 762	1	18	38
22 x 36	559 x 914	1	20	44
24 x 24	610 x 610	1	15	32
24 x 36	610 x 914	1	21	47
30 x 30	762 x 762	1	22	47
30 x 48	762 x 1219	2	32	71
36 x 36	914 x 914	2	30	65
WALL ONLY BELOW				
36 x 48	914 x 1219	2	42	93
48 x 48	1219 x 1219	2	57	125
48 x 60	1219 x 1524	2	71	155

Clear Opening = Width minus 4-1/4" (108mm),
Height minus 1-1/2" (39mm)
Other sizes available upon request for all Models.

Second dimension given is the hinge side
(shown in **Bold**) unless otherwise specified.

This model also available in
2 hour rating.
For wallboard bead model—see FDPW



Intertek

FIRE-RATING INFORMATION

Intertek Warnock Hersey Listed and Labeled:
3 Hour Fire Rating for vertical and horizontal installation
Temp Rise Max: 43° C / 77° F at 30 Min 149° C / 268° F
at 60 Min

Testing Standards:

Vertical: NFPA 252, UL 10B, CAN/ULC S10 4
Horizontal: UBC 43-7, CAN/ULC S112

Optional Smoke Gasket Testing Standards: UL 1784 per
NFPA 105, ASTM E152, CAN4 S106, UBC
7-2, UL 10 (b) NFPA 252 (90- minute)

LATCH AND LOCK OPTIONS

Standard 1/4" Allen Key (A) Optional Knurled Knob (KK)



For detailed specifications see submittal sheet

For a complete list of options visit
www.BestAccessDoors.com

PROJECT DATA

Custom Sizes Available - Fast!

PROJECT NAME :	QTY	W	H	OPTIONS
ARCHITECT :				
DEALER :				
CONTRACTOR :				
LOCATION :	SPECIAL INSTRUCTIONS :			
DATE :	SUBMITTAL APPROVAL :			
TAGGING INSTRUCTIONS :	(signature or stamp)			

Scan or Click



To view Pricing and
Additional Product Info.

TELEPHONE:
1-800-483-0823
FAX:
1-888-828-6021



228 PARK AVE. S. #76520
NEW YORK, NY, 10003



WEBSITE:
www.BestAccessDoors.com
E-MAIL:
info@bestaccessdoors.com

BA-FD3RF

3 HOUR FIRE-RATED ACCESS PANEL WITH RECESSED FLANGE

