



Quality Access Doors- **FAST!**

APPLICATIONS

Installation required roof pitch
15°-90° (4/12 - vertical) on brackets

FEATURES

- **Superior Lighting:** The non-opening design allows for larger glazing units, providing excellent natural light and a clear view of the external environment.
- **Enhanced Safety:** The sash is securely fixed in the frame with screws, ensuring there is no possibility of opening, making it safe for installation at low heights above the floor.
- **Thermal Insulation:** The advanced structure and triple-glazed units offer excellent thermal insulation, helping to maintain a comfortable indoor temperature.
- **Altitude Suitability:** Standard glazing units are suitable for installations up to 3,000 feet above sea level.
- **Flexible Roof Pitch Compatibility:** Suitable for roof pitches between 15 and 90 degrees, making it versatile for various roof designs.
- **European Installation Method:** The window frame sinks below the roof deck to minimize thermal bridging, enhancing energy efficiency.
- **Additional Insulation:** Best combined with thermo flashing, which adds extra insulation to the outside of the window frame. (sold separately)
- **Custom Sizes Available:** Contact us at sales@fakrousa.com for custom size options to fit your unique requirements.
- **Warranty:** Enjoy peace of mind with a 10-year warranty on your FNP P5G window.

SUBMITTAL/TECHNICAL DATA SHEET

SKU: **BA-FNP**

TRIPLE-GLAZED NON-OPENING WOODEN ROOF WINDOW



DIMENSIONS AND APPEARANCE

>> [CLICK TO VIEW ADDITIONAL DETAILS AND PRICING <<](#)

FEATURES:

Frame materia	Pine - Pressure Treated
Frame finish	Two layers of clear acrylic lacquer
Glazing	P5G - Low-E tempered over laminated triple-pane glazing unit with warm TGI spacer and Krypton gas
Warranty	10 years for roof windows 20 years for laminated glass against hail (restrictions apply) 10 years for glass seal

ADDITIONAL PRODUCTS TO BE USED:

Flashings	EHV-AT - for roof tiles, corrugated metal and standing seam ELV-T - for shingles and shakes EBV-P for steel panel sheet
Included mounting accessories	Installation brackets Screws Nails Pencil
External accessories	AMZ solar awning blind

DIMENSIONS:

Size				
		22/39	31/47	31/56
Rough opening (WxR)	in.	22½ x 39½	31½ x 47½	31½ x 56½
Outside frame (SxL)	in.	21½ x 38⅝	30½ x 46½	30½ x 55⅝
Daylight area (glass)	sq. ft m2	3.12 0.29	6.35 0.59	7.75 0.72

For more details see the second page



For a complete list of options visit
www.BestAccessDoors.com

PROJECT DATA

Custom Sizes Available - Fast!

Scan  or  Click



To view Pricing and
Additional Product Info.

PROJECT NAME :	QTY	W	H	OPTIONS
ARCHITECT :				
DEALER :				
CONTRACTOR :				
LOCATION :	SPECIAL INSTRUCTIONS :			
DATE :				
TAGGING INSTRUCTIONS :	SUBMITTAL APPROVAL : (signature or stamp)			

TELEPHONE:
1-800-483-0823
FAX:
1-888-828-6021



228 PARK AVE. S. #76520
NEW YORK, NY, 10003



WEBSITE:
www.BestAccessDoors.com
E-MAIL:
info@bestaccessdoors.com



BA-FNP

TRIPLE-GLAZED NON-OPENING WOODEN ROOF WINDOW

TECHNICAL PARAMETERS:

Technical parameters	Glazing unit type		
	Unit	G53	Rating
U-factor	[BTU/h ft²F]	0.29	NFRC 100 / NFRC 200
Solar Heat Gain Coefficient	-	0.17	NFRC 100 / NFRC 200
Air Leakage	[cfm/ft²] @ 1.57 psf, tested size 46x46	-	NAFS 2017 & CSA A440S1:19
Visible Transmittance	-	0.33	NFRC 100 / NFRC 200
UV protection	-	99.8	EN 410-2011
Condensation Resistance	-	67	NFRC 100 / NFRC 200
Water Penetration Resistance Test Pressure	[Pa]	720	NAFS 2017 & CSA A440S1:19

