

SAFETY FIRST

Caution is the key when working in high elevations and that is where most roof and ceiling access is found. Our Safety Rails are designed for all Roof Hatch applications to assist in making every work space as safe as possible.

FEATURES

- Railing system surrounds all sides of the opening
- (Self Closing Gate) Spring tension gate keeps the opening closed after pass through
- Easy to install
- Safé, easy and economic access
- · Assembled on site, no special tools necessary
- Standard Finish is Safety Yellow Painted, also available in Galvanized

COMPONENTS

MATERIAL: Steel ASTM A36

RAILS: Steel ASTM A36

JOINERS: Steel ASTM A36

RAIL WIDTH: Various lengths to fit the multiple sizes of openings

WEIGHT: Standard rail lengths range from 8lbs. to 11lbs.

COMPLIANCE

- Designs complying OSHA standards
- Other specifications available

For a complete list of options visit www.BestAccessDoors.com

Scan or (m) Click

SUBMITTAL/TECHNICAL DATA SHEET

SKU: BA-RGS SAFETY ACCESSORIES

ROOF HATCH RAIL SYSTEM




■ DIMENSIONS AND APPEARANCE


>> CLICK TO VIEW ADDITIONAL DETAILS AND PRICING <<

DOOR SIZE W x H		WEIG	WEIGHT	
INCHES	(MM)	LBS	KG	
24 x 24	(610 x 610)	60	24.2	
24 x 30	(610 x 762)	70	31.8	
24 x 36	(610 x 914)	75	34.0	
30 x 30	(762 x 762)	80	36.4	
30 x 36	(762 x 914)	90	41.0	
42 x 42	(1067 x 1067)	125	56.8	
48 x 48	(1220 x 1220)	155	70.4	
48 x 72	(1220 x 1829)	210	95.3	
60 x 60	(1524 x 1524)	220	98.9	

For detailed specifications see submittal sheet

MANUFACTURED BY ACUDOR





QTY

SPECIAL INSTRUCTIONS

SUBMITTAL APPROVAL:

(signature or stamp)

Railing product image shown with 36"x 36" Aluminum Roof Hatch.

Roof Hatch products are sold seperately

PROJECT DATA

PROJECT NAME

TAGGING INSTRUCTIONS:

ARCHITECT: DEALER CONTRACTOR LOCATION :

DATE

Custom Sizes Available - Fast!



To view Pricing and Additional Product Info.



TELEPHONE:
1-800-483-0823
FAX:
1_000_020_6021







WEBSITE: www.BestAccessDoors.com

OPTIONS





BA-RGS

ROOF HATCH GUARD SYSTEM SAFETY RAILS - OSHA

