



SPECIFICATIONS

1. FRAME W/ FLASHING (CORNERS FULL WELDED)
 - 20VM - 14 GAUGE P.B. GALV. STEEL
 - 50VM - 11 GAUGE ALUMINUM
2. PINTLE HINGE
3. GASKET (ALL AROUND COVER)
4. COVER GAUGE
 - 20VM - 14 GAUGE P.B. GALV. STEEL
 - 50VM - 11 GAUGE ALUMINUM
5. COVER LINER
 - 20VM - 22 GAUGE P.B. GALV. STEEL
 - 50VM - 18 GAUGE ALUMINUM
6. LIFTING MECHANISM WITH REINFORCED COMPOSITE TUBES AND COMPRESSION SPRINGS
7. 1" RIGID FIBERGLASS INSULATION
8. SLAM LATCH
9. INSIDE AND OUTSIDE HANDLES W/ PADLOCK HASPS
10. ARM GUIDE BRACKET
11. 1" THICK FIBERGLASS COVER INSULATION
12. HOLD OPEN ARM W/ RED VINYL GRIP
13. NEOPRENE GASKET
14. LOCK STRIKE & PADLOCK HASP
15. ANCHOR TABS (QTY & LOCATION VARIES W/ SIZE)
16. GUIDE ARM (IF REQ'D)

SHOP FINISH:

STEEL: RED OXIDE PRIMER
 ALUMINUM: MILL FINISH
 HARDWARE: ZINC PLATED & CHROMATE SEALED
 (UNLESS OTHERWISE SPECIFIED)

THIS PRODUCT MAY BE INSTALLED ON EITHER A FLAT OR SLOPING ROOF. WHEN INSTALLED ON A SLOPE, THE HINGE SIDE MUST RUN PARALLEL WITH THE SLOPE. IF SLOPE EXCEEDS 30°, ADVISE FACTORY FOR MODIFICATION.

CUSTOMER:

P.O. N°

JOB:

SALES REP:



www.BestAccessDoors.com
 Tel.: 1-800-483-0823
 Fax: 1-888-828-6021
 Email: sales@bestaccessdoors.com

SINGLE LEAF ROOF SCUTTLE - TYPE VM

QTY	TYPE	QTY	TYPE	SIZE
				WIDTH x LENGTH
<input type="checkbox"/>	S-20VM	<input type="checkbox"/>	S-50VM	3'-0" x 2'-6" [914mm] x [762mm]
<input type="checkbox"/>	E-20VM	<input type="checkbox"/>	E-50VM	3'-0" x 3'-0" [914mm] x [914mm]
<input type="checkbox"/>	NB-20VM	<input type="checkbox"/>	NB-50VM	2'-6" x 4'-6" [762mm] x [1370mm]
<input type="checkbox"/>	L-20VM	<input type="checkbox"/>	L-50VM	2'-6" x 8'-0" [762mm] x [2440mm]
<input type="checkbox"/>	EW-20VM	<input type="checkbox"/>	EW-50VM	3'-3 3/8" x 3'-3 3/8" [1000mm] x [1000mm]